



**SCOFIELD  
SYSTEMS**

www.scofield.com

## LITHOCHROME<sup>®</sup> Color Hardener, LITHOCHROME<sup>®</sup> Antiquing Release & SCOFIELD<sup>®</sup> Texturetop

### PRODUCT DESCRIPTIONS:

**LITHOCHROME Color Hardener** is a dry-shake colored hardener formulated to be easily incorporated into the surface of freshly placed concrete.

**LITHOCHROME Antiquing Release** is a powdered, colored bond breaker used when imprinting with mat-type texturing or stamping tools.

**SCOFIELD Texturetop** is a trowelable cementitious topping for resurfacing and texturing nonmoving, interior or exterior concrete floors or hardscapes.

**LITHOCHROME<sup>®</sup> Colorwax<sup>™</sup>** curing compound and **COLORCURE<sup>®</sup> Concrete Sealer** are available in matching colors.

### Additional colors available:


A-11 Concrete Gray, 6016 White, 0510 Black.

Some colors are made to order. Check price list for availability, pricing and possible minimum quantities.

Review Tech-Data Bulletins and MSDS before use. Visit [www.scofield.com](http://www.scofield.com) for the most current versions.



A53 Arizona Tan



0266 Ash White\*



1138-S Blue Smoke+SS



A59 Beige Cream\*



0588 Blush Beige\*



A26 Brick Red



1139 Burberry Beige\*



A33 Classic Gray



A27 Dark Red



A21 Deep Charcoal



A25 La Crescenta Brown



3611 Oyster White\*



A65 Pecan Tan



A57 Platinum Gray



A24 Russet



A85 Muted Green



A50 Slate Gray



4948 Smoke Beige\*



A51 Steadman Buff



5183 Stone Gray\*



A29 Terra Cotta



A28 Tile Red



5921 Walnut



5758 Weathered Sage\*

**COVERAGE RATE FOR COLOR HARDENER:** Coverage rates vary with intended use and application. LITHOCHROME Color Hardener should be applied at a rate of 50 lb (1 bag) per 100 ft<sup>2</sup> (2.5 kg/m<sup>2</sup>), except where indicated by an asterisk (\*).

\*Denotes colors requiring a higher coverage rate, where Scofield recommends 90-120 lb per 100 ft<sup>2</sup> (4.5-6.0 kg/m<sup>2</sup>). See reverse for more information.

+SS = Check current market price.

Colors are approximate and best viewed in daylight. Colors shown represent the use of LITHOCHROME Color Hardener with a flat-troweled finish which has been cured with color-matched LITHOCHROME Colorwax or COLORCURE Concrete Sealer.

L. M. Scofield Company 1 800 800 9900



Gary

**GROH**

Construction LLC

www.grohconcrete.com

(507) 437-2524

FOR PROFESSIONAL USE ONLY